LABORATORIES

- LONG LASTING
- DISTILLED FROM ORGANIC PLANT AND VEGETABLE MATERIAL.
- CONTAINS NO PETROLEUM DISTILLATES.

Lift Station Maintainer is one of UNITED's Solar Solvent products, especially designed to clean and deodorize lift stations. The superior solvency of the product cuts grease and slime from the sidewalls of the station while the fresh smelling orange oils of the base deodorize even the most malodorous facilities.

DIRECTIONS:

Add sufficient material so that 1'' (2.5 cm) or 2'' (5.1 cm) of material floats on the surface of the water. This material will dissolve and solubilize grease accumulations in the lift station, as well as the grease accumulation on the side walls where it comes in contact.

Ask your United Representative for your suggested weekly maintenance dose. The recommended maintenance dose (1/4 of your initial dose per week) is strictly a suggested starting point. Conditions of use and load requirements may cause this to vary widely.

IMPORTANT:

Be sure float is solvent resistant and is set, so the water level never goes to the point where the station is completely pumped out. Enough water should always remain in the station, to keep this maintainer intact. Submersed pumps and wiring must be solvent resistant. Lift Station Maintainer will attack plastics, rubber, neoprene and soft materials. DO NOT USE Lift Station Maintainer IN A TURBULENT LIFT STATION.

When using a metering pump with this product, you must use Viton® tubing.

For food plant and other industrial use, avoid contamination of food in the application and storage of the product. Do not use in food handling areas.

United 493

Lift Station Maintainer

WARNING KEEP OUT OF REACH OF CHILDREN. See other cautions on back/side panel.

PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By: UNITED LABORATORIES, INC. 320 37th Avenue • St. Charles, IL 60174 1-800-323-2594 • www.unitedlabsinc.com WARNING: Flammable liquid and vapor. Keep away from heat/ sparks/open flames/hot surfaces.

- No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/ protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction. Store in a wellventilated place. Keep cool. Dispose of contents/container to an approved waste disposal plant.

FIRST AID MEASURES:

IF IN EYES: Immediately flush with plenty of water for up to 15 minutes. Get prompt medical attention.

IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse. If symptoms develop, seek medical attention.

IF INHALED: Remove to fresh air. If symptoms develop, seek medical attention. If not breathing, give artificial respiration.

IF SWALLOWED: Do not induce vomiting. Get medical attention immediately. If vomiting occurs, have victim lean forward to reduce risk of aspiration.

CONTAINS (CAS#): D-limonene (94266-47-4)

