

United 856

BIO-ACCEL

for Grease and Odor Control
in Wastewater Environments

Featuring Patented  Inter-Core
Technology®

Moving Biological Water Treatment Generations Ahead

The improved **BIO-ACCEL** utilizes Inter-Core Technology® to provide you with the combined staying power of proven block technology and the instant concentrated dosage of a granular active.

BIO-ACCEL contains a critical blend of enzymes (10,000 IU/gram) that act as a catalyst to accelerate biodegradation of grease and other organic waste in lift stations, grease traps and mains. The inner core of the block is quickly released to jump start the biodegradation, while the outer core of **BIO-ACCEL** continues to provide slow release performance for 60 – 180 days, depending on flow rates.

The performance of **BIO-ACCEL** is not affected or limited by pH levels, temperature changes or the amounts of disinfectants or petrochemicals found in the water which can often affect the performance of many bacterial products.

BIO-ACCEL provides you with a responsible solution for your needs:

- Earth Smart® formulation.
- No hazardous components and is ranked zero in all HMIS numbers.
- VOC-free and non-toxic.
- Non-flammable.
- Near neutral pH.
- Works at temperature range of 38° – 165°F (3° – 74°C), with an optimal range of 65° – 110°F (18° – 43°C).
- Safe for plant and process applications and will enhance bacterial process in the plant.
- Ideal for lift stations and grease traps.



Before



After

