

UNITED

LABORATORIES

United 961 Non-Ammoniated Polymer Solvent has a wide variety of applications in industry for the removal of unwanted polymers and alums.

- **NON-FLAMMABLE • NON-ACID**
- **CONTAINS NO PETROLEUM DISTILLATES.**

In wastewater treatment facilities, **United 961 Can Be Used On:**

- Spills • Partially clogged or sluggish lines • Sluggish pumps
- Blinded press belts, sticky rollers, stiff gaskets, and press frame
 - Blinded reactor chambers • Residual in centrifuges
- Holding and mixing tanks • Media for plate and frame presses
 - Vacuum filters - coil or other media.

DIRECTIONS:

NEVER USE UNITED 961 UNDILUTED. (Polymers are water activated. Therefore, clean-up requires a dilution.)

FOR SPILLS FOR ALL NON-EMULSION POLYMERS: (Bucket and Broom)

1. Saturate the spill with COLD water. Filtrate or potable water may be used. 2. Dilute **United 961** (10 to 1) with COLD water. 3. Apply to the affected area. 4. Agitate with a natural bristle broom that has been soaked in the diluted **United 961** solution. (To clean up the broom when finished, rinse the broom alternately with the dilute **United 961** solution and COLD water until clean and free from polymer residual.) 5. Rinse cleaned area thoroughly with COLD water.

FOR SPILLS FOR ALL NON-EMULSION POLYMERS: (High Pressure Washer)

1. Saturate the spill with high pressure COLD water. 2. Apply **United 961** (30 to 1) with COLD water. Filtrate or potable water may be used. 3. Rinse with high pressure machine using COLD water. 4. Repeat if necessary.

FOR SPILLS FOR EMULSION POLYMERS: (Bucket and Broom)

1. Dilute **United 961** (10 to 1) with COLD water. 2. Apply to affected area. 3. Agitate with natural bristle broom. 4. Allow agitated material to sit for 20-30 minutes. 5. Now continue as for non-emulsion polymers steps 1-5.

FOR BELT FILTER PRESS CLEANING:

For best and quickest results use **United 961** (at 30 to 1 dilution rate) with COLD water through a high pressure washer.

1. Thoroughly saturate the press with water or wash the press directly after the washing cycle built into the machine. 2. Start the cleaning process with the rollers. Use 30 to 1 dilution rate of **United 961** allowing each roller to rotate 360°. Repeat with each roller. 3. Clean gaskets top and bottom with the wand of the pressure washer using **United 961** at 30 to 1. 4. Proceed to the belts starting with the bottom belt at the zipper. Allow the belt to rotate 360°. Rinse thoroughly. 5. Repeat the process with the top belt.

United 961 may be injected directly into the belt press wash cycle to achieve a use rate of 1 part **United 961** to 200 parts water.

FOR PLATE AND FRAME PRESS CLEANING:

1. Soak press plates thoroughly with COLD water using a high pressure washer. 2. Apply **United 961** at a dilution rate of 30 to 1 to the back and front of each plate. 3. High pressure rinse with COLD water.

United 961

Non-Ammoniated Polymer Solvent

DANGER
KEEP OUT OF REACH OF CHILDREN.
See other cautions on back/side panel.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS: (continued)

FOR LINE CLEANING FOR ALL NON-EMULSION POLYMERS:**

1. Rinse lines to be cleaned with COLD water. 2. Empty water rinse from the lines. 3. Fill the lines with **United 961** at a 10 to 1 dilution rate and circulate (5 min.) or let stand (30 min.) 4. Rinse with COLD water. Occasionally a second application is needed.

FOR PUMP CLEANING FOR ALL NON-EMULSION POLYMERS:**

1. Isolate pump from the system or clean it in conjunction with line cleaning. 2. Draw out as much of the polymer from the pump as you can by the action of the pump. 3. Circulate COLD water for 5 minutes. 4. Use **United 961** at a dilution rate of 10 to 1 and circulate for 5 minutes or let stand for 30 minutes.

****FOR EMULSION POLYMERS DO ONE MORE STEP.** First introduce a (10 to 1) dilute solution of **United 961** into the line or pump and allow the solution to sit 20 to 30 minutes. Empty the resulting solution from the system. Then follow steps 1 - 4 for cleaning lines and pumps for NON-EMULSION POLYMERS.

For application on the wastewater process side. Please contact our technical services group for assistance.

DANGER: Causes severe skin burns and eye damage.

Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves, protective clothing, eye protection, face protection. Do not breath dust, fume, mist, vapors, spray.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician. **IF ON SKIN (or hair):** Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a poison center or doctor/physician. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. **IF SWALLOWED:** Rinse mouth. Do not induce vomiting. Immediately call a poison center or doctor/physician.

Store locked up. Dispose of contents/container to an approved waste disposal plant.

CONTAINS (CAS#): Monoethanolamine (141-43-5), Proprietary (Proprietary)

An SDS for this product is available through United's website, www.unitedlabsinc.com. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

