



UNITED

LABORATORIES

Mask, Break and Eliminate H₂S within Fifteen Minutes with KONVERT-A-ZYME.

- Disperses completely in water with no residue or precipitate from product.
- Provides flocculent properties.
- Catalyzes the breakdown of wastes and helps control grease build-up.
- Ideal for use in wastewater treatment plants, lagoons and drying beds.
- Fresh, mild vanilla scent masks odors to immediately control problem.

Earth Smart® Formulation Means There Are No Environmental or Safety Hazards.

- No hazardous components, no VOCs, ranked zero in all HMIS categories.
- Non-toxic according to EPA, OSHA, NIOSH and WHMIS standards.
- Non-flammable. Will not burn.
- Near neutral pH.
- No material safety handling or closed space problems.

For application on the wastewater process side. Please contact our technical services group for assistance.

DIRECTIONS:

Dilution rates will vary based upon the level and type of odor being controlled, the application method and the area to be treated.

For In-Line Injection: Use one part **United 893** per 50,000-100,000 parts of raw influent. To determine exact dilution rates, do a bench test.

For Misting with Spray Heads or Spray Bars: Dilute 1 part **United 893** to 100-300 parts of water in the dilution tank and spray continuously or activate by timer as needed. Use a fine mist to improve coverage.

For Fogging Applications: Mix a 100-200:1 solution in an empty drum and attach an A187 TRI-JET Fogger. An A185 Timer will control the activation of the fogger. Always allow a 15-minute cool-down period per hour with the TRI-JET Fogger.

United 893

KONVERT-A-ZYME Wastewater Control and Degassing Agent

**KEEP OUT OF REACH OF CHILDREN.
See other cautions on back/side panel**

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

**Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com**

DIRECTIONS: (continued)

For Sludge Odor Control on Belt Presses: Use one part **United 893** per 50,000-100,000 parts of 3% sludge. Less polymer may be needed.

For Sludge Odor Control on Land: Use one to five parts in the terragitator per 50,000-100,000 parts of liquid sludge to be spread. To determine exact dilution rates, do a bench test.

PRECAUTIONS:

Avoid contact with skin and eyes.

FIRST AID MEASURES:

If exposed or concerned: Get medical advice or attention.

IF IN EYES: Flush with cool water for at least 15 minutes and call a physician or poison center.

IF ON SKIN: Wash with soap and plenty of water. If irritation persists, call a physician or poison center.

IF SWALLOWED: Do not induce vomiting unless directed by medical personnel. Seek medical attention immediately. Never give anything by mouth to an unconscious person.

Storage: Keep product in a properly labeled, tightly closed container. Do not allow this product to freeze, as the container may split or rupture.

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.