



UNITED

L A B O R A T O R I E S



United 988 GASTMASTER block that inhibits the production of H₂S gas in collection systems. **GASTMASTER** provides a truly low-maintenance approach to odor and H₂S reduction in lift stations, manholes, mains and sumps. Simply drop it in and replace it with a new one when the block is spent.

The innovative Inter-Core Technology® combines the staying power of proven block technology with the instant concentrated dosage of a granular active.

- The core of the **GASTMASTER** block consists of 10 billion CFU/g count of a special bacterial blend that is released as a slug dose into the waste stream within minutes.
- The exterior of the **GASTMASTER** block is a special blend of bacteria. The 10 billion CFU/g block is designed to release its bacteria over an extended time of 60 to 180 days to continually biodegrade grease and other organic wastes.

FEATURES AND BENEFITS:

- Specifically blended and adapted to reduce H₂S gas accumulation by as much as 30%.
- Earth Smart® Certified.
- Easy installation with minimal ongoing attention.
- Contains facultative anaerobes which work with or without oxygen.
- Block withstands a wide range of temperatures and adverse conditions.

United 988

GASTMASTER

H₂S Inhibitor Block

with Inter-Core Technology®
Patented

KEEP OUT OF REACH OF CHILDREN.
See other cautions on back/side panel.

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DIRECTIONS:

Manholes and Mains: In manhole, **GASTMASTER** should be placed in the U channel nearly vertically on the upstream end of the U channel.

Lift Stations: **GASTMASTER** block should be used in low flow applications. Suspend the block so the entire block is submerged below the water at its lowest level. Apply one block for every 50,000 GPD flow. For flows in excess of 100,000 GPD, please contact your United Representative.

Sumps: **GASTMASTER** block should be suspended in the sump so the block is just under the surface. Apply one block for every 350 gallons capacity. If capacity is over 350 gallons, spread the blocks out in different sections of the sump.

FIRST AID MEASURES:

IF IN EYES: Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

IF ON SKIN: Wash off immediately with plenty of water for at least 15 minutes.

IF INHALED: Not likely an issue. Remove to fresh air.

IF SWALLOWED: Clean mouth with water and drink afterwards plenty of water.

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product.